Innlights

Innlights
Displaysolutions

// www.innlights.de

M-Series Indoor
// High-Precision

// Aluminium-Gehäuse, aus einem Block gefräst
Werkzeuglose Montage
Magnetverschluss-System für LED Module
(Werkzeugloses Tauschen)
LCD Info-Display
Black Face SMD

Neutrik powerCON NAC3
Neutrik Ethercon Datenkabel

// Zertifikate: EMC/EMV, RoHs, CE, TÜV Süd

Pixel Pitch [mm]	3,75	4,8	6
Brightness [cd/m²]		1.300 - 2.000	
Protection Level [Front/Back]		IP43	
Module Size [mm]		480 x 480 x 73	
Module Weight [kg]	8,3	7,5	7,5
Module Resolution [px]	128 x 128	100 x 100	80 x 80
Physical Density [px/m²]	71.111	43.402	27.777
Refresh Rate [Hz]		> 4.800	
LED Type	SMD2121	SMD3528	SMD3528
LED Chip		Epistar (R) / Silan (G,B)	
LED Encapsulation		NationStar	

Module Material	Aluminium
Viewing Angle Hor/Ver [Deg]	140 / 140
Video Processing	Novastar
Refresh Frame Frequency [Hz]	60
Grey Scale	16.384 (14 bit)
Color [Mio]	> 16,7 (24 bit)
Module Wattage Max./Avg. [W]	300 / 120
Input Voltage [V]	110 - 220 (+- 10%)
Operation humidity [RH]	10% - 90%
Working Temp. Min./Max. [°C]	-30 / +40