



Innlights Displaysolutions

// www.innlights.de

X-Series Indoor // Light-Weight

- // Aluminium-Gehäuse
- Werkzeuglose Montage
- Magnetverschluss-System für LED Module (Werkzeugloses Tauschen)
- LCD Info-Display
- Black Face SMD

Neutrik powerCON NAC₃
Neutrik Ethercon Datenkabel

// Zertifikate: EMC/EMV, RoHs, CE, TÜV Süd



Pixel Pitch [mm] 6 9 12

Brightness [cd/m²] 1.800 - 2.500

Protection Level [Front/Back] IP54

Module Size [mm] 576 x 576 x 75

Module Weight [kg] 8,15

Module Resolution [px] 96 x 96 64 x 64 48 x 48

Physical Density [px/m²] 27.777 12.345 6.944

Refresh Rate [Hz] > 4.800

LED Type SMD3528

LED Chip Epistar (R) / Silan (G,B)

LED Encapsulation NationStar

Module Material Aluminium

Viewing Angle Hor/Ver [Deg] 140 / 140

Video Processing Novastar

Refresh Frame Frequency [Hz] 60

Grey Scale 16.384 (14 bit)

Color [Mio] > 16,7 (24 bit)

Module Wattage Max./Avg. [W] 200 / 80

Input Voltage [V] 110 - 220 (+- 10%)

Operation humidity [RH] 10% - 90%

Working Temp. Min./Max. [°C] -30 / +40